

Warming cabinet intended for warming of IV fluids, irrigation solutions, linens and blankets.

## **FEATURES**

- 24h set temperature maintenance
- Uniform warming of fluids and linen
- Fast warming time (20-60 min depending on the set and ambient temperatures)
- Different sizes available (120, 180, 360 lt)
- Dual compartment models
- Stainless steel structure

## **APPLICATION**

Can be installed in pre-operating rooms, nurse's stations, examination and medical treatment rooms, etc.

## **CONTROL SYSTEM**

- LED display
- Indication of current and set temperatures
- Indication of time since heating start
- 2 heating modes: «Solutions» and «Linen»
- Door open indicator
- Audible and visual alarms
- RFID-card for control panel locking
- Self-diagnostic system at the power-up







- Stainless steel shelves
- Extendable and removable shelves for convenient use and easy disinfection of internal surfaces
- Door lock
- Left- or right-hinged door



| MODULAR SYSTEM  Combination of models with control panel for each compartment:  S+S  M+M  M+S  L+S | Thermo S       | Thermo M                   | Thermo L        |
|--|----------------|----------------------------|-----------------|
| Volume   | 120 litres     | 180 litres                 | 360 litres      |
| Dimensions (W $\times$ D $\times$ H )  | 670x640x580 mm | 670x640x840 mm             | 670x640x1450 mm |
| Number of shelves  | 2              | 3                          | 5               |
| Maximum power consumption  | 250 W          | 450 W                      | 700 W           |
| Supply voltage / frequency   |                | 110-230 VAC, 50/60 Hz      |                 |
| Temperature settings   |                | 34°C - 60°C                |                 |
| Temperature increment  |                | 0.5°C                      |                 |
| Average warming time (at an initial t 20°C)<br>- to 34°C<br>- to 42°C<br>- to 60°C                 |                | 20 min<br>35 min<br>60 min |                 |
| Continuous operation   |                | 24h                        |                 |
| Electric shock protection class  |                | B/I                        |                 |
| Protection class   |                | IP23                       |                 |
|  |                |                            |                 |



## **OPTIONS**

- Stationary
- Mobile
- \* Castor wheels with different diameters available

**SCAN ME** 

